



DATE

JOB NAME

TYPE

Features	Applications
----------	--------------

- Fixture components snap together for ease of installation and maintenance
- Knock-outs provided for convenience outlet, pull switch and conduit attachment

- Office Areas
- Retail Stores
- Class Rooms
- Libraries
- Restaurants

Series	Size	Lamps	Watts		Voltage	Options
S	2FT	1	17W T8	32W T8	120	EM-EM Pack 1-Lamp
	3FT	2	14W T5	28W T5	277	EM2-EM Pack 2-Lamp
	4FT	3	24W T5HO	54W T5HO	UNV	DB-Dimming Ballast
	6FT		20W T12	40W T12	(T12 dedicated	SC-Separate Circuit
	8FT		11W LED tubes	22W LED tubes	voltage only)	MS-Motion Sensor
			25W T8	59W T8		WG-Wireguard
			21W T5	86W T8HO		AS-Asymmetric Reflector
		39W T5HO	96 T12		SR-Symmetric Reflector	
		30W T12				

Ordering Example: S-232WT8-UNV-EM

## Details

**Application Features:** Specification grade fluorescent channel. For use in indoor applications where a T8, T5, T5HO, T12 or LED striplight with tool-less design and low cost is required. Available in 2', 3', 4', 6' and 8' lengths.

**Construction:** Die formed 20 ga. cold rolled steel housing. Fixture components snap together for ease of installation and maintenance. Sufficient knock-outs provided for convenience outlet, pull switch and flexible conduit attachment.

**Finish:** Baked white enamel.

**Electronic:** Electronic ballasts are class P, thermally protected.

**Approvals:** Union made, UL listed, and manufactured in the US.

**Options:** Emergency Battery Backup, Dimming Ballast, Separate Circuit, Motion Sensor, Wireguard, Asymmetric Reflector, Symmetric Reflector.

